

WINCHESTER 1300* FOREND TACTICAL GRIP

1. Remove the barrel by unscrewing the magazine end cap or extension and pulling the barrel free from the receiver.

CAUTION-The magazine spring may be released when the end cap or extension is removed.

2. Remove the trigger group from the receiver by first pushing out the pin located just above the trigger on the receiver. Next turn the receiver upside down and pull up on the trigger guard, this will remove the trigger group. Next pull the forend all the way to the rear, then while holding the bolt in the rearward position, pull the forend back forward free from the bolt and off the magazine tube.

3. Using the supplied "T" wrench, unscrew the forend nut and remove the forend.

CAUTION - Be sure not to bend the forend's side rails.

4. Replace the forend with the forend Tactical Grip and securely tighten the nut into place. Note: Remove the nylon ring inside the forend nut before replacing it. You are now ready to reassemble your shotgun by reversing the previous instructions.

*Fits Defender model with 6" Forend tube.

ALL MOSSBERG 500/590 FOREND TACTICAL GRIP

1. Be sure the shotgun is unloaded.

2. Remove the barrel by unscrewing the barrel screw, located at the end of the magazine tube, and pulling the barrel free from the receiver.

3. Remove the forend assembly from the shotgun. This requires removal of the trigger assembly and bolt. Please refer to your Mossberg instruction manual for disassembly information.

4. Using the supplied "T" wrench, unscrew the forend nut and remove the forend.

5. Before replacing the factory forend with the Tactical Forend Grip be aware that Mossberg forend tubes have been made in two lengths. Older models had a 7 3/4" length and newer models are shorter at 6 1/2". Please note that the Tactical Forend Grip has a removable spacer ring on the front. This ring is to be used with the 7 3/4" forend tubes and removed and discarded if your forend tube is 6 1/2" long.

6. Once you have determined if you require the spacer ring or not, slide the Tactical Forend Grip onto the forend tube and securely tighten the forend nut in place. You are now ready to reassemble your shotgun by reversing the above steps.

Note: Does not fit Maverick shotguns.

REMINGTON 870 FOREND TACTICAL GRIP

1. Remove the barrel by unscrewing the magazine end cap or extension and pulling the barrel free from the receiver.

CAUTION-The magazine spring may be released when the end cap or extension is removed.

2. With slight forward pressure being applied to the forend, depress the primary shell-stop. (You will feel the forend and slide assembly move forward slightly). Depress the secondary shell-stop which allows the bolt assembly to be removed from the shotgun.

3. Set the bolt assembly aside. Using the supplied "T" wrench, unscrew the forend nut and remove the forend.

CAUTION-Be sure not to bend the forend's side rails.

4. Replace the forend with the forend Tactical Grip and securely tighten the nut in place. You are now ready to reassemble your shotgun by reversing the previous instructions.