

## Barrel Specifications

	Bore	Groove	Twist	Suggested Ball Dia.
Plains Pistol .50	.501"	.520"	1/30"	.490"/.495"
Plains Pistol .54	.541"	.560"	1/30"	.530"/.535"
Great Plains Rifle .50	.502"	.520"	1/60"	.490"/.495"
Great Plains Rifle .54	.542"	.558"	1/60"	.530"/.535"
Great Plains Hunter .50	.502"	.510"	1/32"	*
Great Plains Hunter .54	.542"	.550"	1/32"	*
Trade Rifle .50	.502"	.520"	1/48"	.490"/.495"
Trade Rifle .54	.542"	.558"	1/48"	.530"/.535"
Deerstalker .50	.502"	.520"	1/48"	.490"/.495"
Deerstalker .54	.542"	.558"	1/48"	.530"/.535"
Deerstalker Stainless Steel .50	.502"	.510"	1/48"	*
Deerstalker Stainless Steel .54	.542"	.550"	1/48"	*

**\*Note:** Recommend conical or sabots for this model.

**Note:** These are nominal specifications for general information only. The actual dimensions of a given gun may vary several thousandths of an inch. It is often necessary to experiment with several ball diameters and patch thicknesses to find the one best for your application. If you have any questions concerning your gun, please note the serial number of your gun and call/write Lyman Customer Service for verification.

All barrels are 15/16" across the flats.